



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 061 356 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
20.12.2000 Bulletin 2000/51

(51) Int. Cl.⁷: **G01N 21/53, G01N 21/85**

(21) Application number: **00304861.8**

(22) Date of filing: **08.06.2000**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **14.06.1999 US 333181**

(71) Applicant:
**GENERAL ELECTRIC COMPANY
Schenectady, NY 12345 (US)**

(72) Inventors:
• **Dean, Anthony john
Scotia, New York 12302 (US)**
• **Shapiro, Andrew Philip
Niskayuna, New York 12309 (US)**

(74) Representative:
**Pedder, James Cuthbert et al
GE London Patent Operation,
Essex House,
12/13 Essex Street
London WC2R 3AA (GB)**

(54) **In-line particulate detector**

(57) An in-line particulate detector comprises a housing (102) having an inner flow portion. The housing (102) is disposed between adjacent portions of pipeline (50) to permit a fuel flow from a fuel source (56) through the inner flow portion to a fuel consumer (10). A light source (104) is positioned within the housing (102) for emitting a light beam within the inner flow portion. A first photodetector (106) is positioned within the housing (102) to detect the full strength of the light beam (110). A second photodetector (108) is positioned within the housing (102) to detect low, baseline levels of the light beam (110). Circuitry (114) is coupled to first and second photodetectors (106, 108) to monitor the ratio of light intensities. When a fuel containing particulates is introduced, the light beam (110) is scattered and the intensity measured by the second photodetector (108) will increase and the intensity measured by the first photodetector (106) will decrease.




FIG 2

Description

[0001] This invention relates generally to particulate detectors and more specifically to in-line particulate and liquid droplet detectors for natural gas lines.

[0002] Industrial power generation gas turbine engines include a compressor for compressing air that is mixed with fuel and ignited in a combustor for generating combustion gases. The combustion gases flow to a turbine that extracts energy for driving a shaft to power the compressor and produces output power for powering an electrical generator, for example. The turbine is typically operated for extended periods of time at a relatively high base load for powering the generator to produce electrical power to a utility grid, for example. Exhaust emissions from the combustion gases are therefore a concern and are subjected to mandated limits.

[0003] Low emission combustion systems are designed to produce low emissions and high combustion efficiency while burning natural gas fuel that is assumed to be free of liquid or solid contaminants. In fact, pipeline gas is at times contaminated with condensed liquid hydrocarbons (to varying degrees) as well as other solid particulate contaminants. It is highly desirable to minimize the effects of these contaminants on gas turbine combustor performance, either by their removal or by robust combustor design. As low emission systems have become more prevalent in the field and exposed to a variety of natural gas sources while performing with lower and lower emission goals, the presence of varying amounts of liquid hydrocarbons in the fuel source has become an increasingly important operational issue.

[0004] The quality of natural gas supplied to gas turbines is an important variable in turbine performance. The principle component of natural gas is methane, which typically accounts for over 90% of the mass. Other components in natural gas may include heavier hydrocarbons, oils and water. In gas turbines equipped with combustors that premix fuel and air prior to ignition, the chemical composition of the gas is particularly important because of the potential for ignition to occur within the mixing zone. The effect of heavier hydrocarbons and oils in the gas stream is to lower the autoignition temperature of the mixture. Natural gas with high concentrations of these species is more likely to ignite in the mixing zone of the combustors than in an intended flame holder region.

[0005] Several approaches have been utilized to detect particulates or droplets in a gas pipeline including, for example, light scattering, acoustics, eddy currents, and capacitance methods. Most current approaches, however, require a slip-stream of a total flow for samples and therefore may not be representative of the entire flow. Additionally, most current instruments are rather delicate, expensive and are typically not robust enough for long-term application in a gas

pipeline and cannot be placed directly into a pipeline.

[0006] Accordingly, there is a need in the art for an improved particulate detector.

[0007] In one embodiment of the invention, an in-line particulate detector comprises a housing having an inner flow portion. The housing is disposed between adjacent portions of pipeline to permit a fuel flow from a fuel source through the inner flow portion to a fuel consumer. A light source is positioned within the housing for emitting a light beam within the inner flow portion. A first photodetector is positioned within the housing to detect the full strength of the light beam. A second photodetector is positioned within the housing to detect low, baseline levels of the light beam. Circuitry is coupled to first and second photodetectors to monitor the ratio of light intensities. When a fuel containing particulates is introduced, the light beam is scattered and the intensity measured by the second photodetector increases and the intensity measured by the first photodetector decreases.

[0008] The invention will now be described in greater detail, by way of example, with reference to the drawings, in which:-

FIG. 1 is a schematic, cross-sectional side elevation view of a pipeline and an in-line particulate detector in accordance with one embodiment of the instant invention;

FIG. 2 is an enlarged schematic cross-sectional side elevation view of an in-line particulate detector in accordance with one embodiment of the instant invention; and

FIG. 3 is a schematic, cross-sectional side elevation view of a pipeline and a remote in-line particulate detector in accordance with one embodiment of the instant invention.

[0009] A pipeline 50 comprising an inlet 52 and an outlet 54 provides fluid communication between a fuel source 56 and a fuel consumer 10, for example a power turbine as shown in Fig. 1. A shut off valve 58 is typically disposed within pipeline 50, which valve 58 is movable between a fully open position and a fully closed position to allow or prevent fuel flow, respectively, from fuel source 56 to fuel consumer 10.

[0010] As discussed above, detecting that a proper fuel quality is present, prior to combustion within fuel consumer 10 is becoming increasingly important.

[0011] In accordance with one embodiment of the instant invention, an in-line particulate detector assembly 100 is coupled to pipeline 50. Typically, although not necessarily, in-line particulate detector assembly 100 is embodied within a housing 102, for example a flange, that is disposed between adjacent portions of pipeline 50 to permit a continuous fuel flow 60 from fuel source 56 to fuel consumer 10. In-line particulate detector

assembly 100 may also be directly positioned within a sidewall of pipeline 50.

[0012] In-line particulate detector assembly 100 comprises housing 102, a light source 104, a first photodetector 106 and a second photodetector 108, as shown in FIG. 2.

[0013] Light source 104 is positioned within housing 102 so as to enable light source 104 to emit a light beam 110 within an interior flow portion 112 of housing 102. First photodetector 106 is disposed opposite light source 104 so as to be optically coupled with light source 104. Typically, first photodetector 106 is disposed within housing 102 opposite and substantially normal to light source 104 such that most of the full strength of a generated light beam 110 is detected by first photodetector 106 when little or no particles or other interfering substances are located within interior flow portion 112 of housing 102.

[0014] Second photodetector 108 is positioned within housing 102 adjacent to first photodetector 106. Second photodetector 108 is angularly offset from the normal unimpeded path of light between light source 104 and first photodetector 106, typically in the range between about 10° to about 60°. A key feature of this invention is the placement of second photodetector 108 slightly offset from light source 104. This offset position maximizes the collection of scattered light while retaining the simplicity of a single photodetector for scattered light detection.

[0015] When little or no particles or other interfering substances are present within a fuel flow 60 traveling through interior flow portion 112 of housing 102, second photodetector 108 will sense a baseline level of light reflected from first photodetector 106 and Rayleigh scattering from gas molecules within fuel flow 60 (Fig. 1).

[0016] When particles or other interfering substances are present within fuel flow 60 flowing through interior flow portion 112 (Fig. 2) of housing 102, light beam 110 will be scattered by these particles and the light intensity reaching second photodetector 108 will increase above the baseline level and light intensity reaching first photodetector 106 will decrease. The ratio of light intensities indicated by first and second photodetectors 106, 108 provides a sensitive measure of the presence of particles and the amount of particles in fuel flow 60.

[0017] Typically, fuel flow 60 comprises a natural gas, for example, methane, or propane, hexane, heptane, gas derived from coal, or the like. As discussed above, fuel flow 60 flows from fuel source 56 to fuel consumer 10 through pipeline 50 and interior flow portion 112 of housing 102.

[0018] Circuitry 114 is coupled to first and second photodetectors 106, 108 to measure the presence and quantity of particles when exposed to a fuel flow 60 between inlet 52 and outlet 54.

[0019] In one embodiment, circuitry 114 includes a

power input, an amplifier and a processor for monitoring the signals from first and second photodetectors 106, 108 and generating an output signal. In another embodiment, circuitry 114 further comprises an amplifier and a computer for processing signals and generating a particulate level report or display.

[0020] A control structure is inputted into circuitry 116, for example, by programming into memory of an application specific integrated circuit (ASIC) or is embedded in the form of algorithms in one or more computers 119 such as a work station. Other types of computers can be used, however, such as a minicomputer, a microcomputer, or a supercomputer, for example. The programming or algorithm performed may be programmed in C, C++, JAVA, Basic, MATLAB, FORTRAN, or other programming languages.

[0021] If the ratio of light intensities indicated by first photodetector 106 and second photodetectors 108 is above a setpoint, indicating contamination, circuitry 114 may initiate a system control. For example, limit fuel consumer 10, to low load operation. Additionally, if the ratio of light intensities rises above a setpoint, circuitry 114 may initiate an algorithm to look at combustion system anomalies, or, for example, sound an alarm or otherwise alert a system user.

[0022] While the instant invention is shown connected to a pipeline 50 for a fuel consumer 10, this invention could also be applied to monitor the quality of process gases, not necessarily intended for combustion. Additionally, the instant invention can be utilized for monitoring gas quality at the exit of a cryogenic gas processing system; monitoring gas quality at the custody transfer point between a gas producer and a gas transmission company; monitoring gas quality at the custody transfer point between a gas transmission company and a local distribution company; monitoring gas quality at a compressor station used to compress gas for natural gas powered vehicles, or the like.

[0023] Light source 104 may comprise a laser diode light source or the like. The advantage of laser light over a collimated beam of non-laser light is the combination of low divergence angle with high intensity and relatively high electrical efficiency. Light can be collimated from a conventional light source by spacing two slits far apart, however, the intensity is low relative to the power generated by the source.

[0024] Photodetectors 106, 108 may comprise photodiodes or the like. The advantage of solid state photodiodes is that they are inexpensive, very compact, and durable. While photodiodes are not as sensitive as traditional photomultiplier tubes, with proper amplification, the sensitivity of photodiodes is sufficient to sense low levels of particles.

[0025] In one embodiment, a light trap is disposed adjacent first photodetector 106 to minimize the light reflected therefrom.

[0026] In one embodiment, ball valves 116 and sight glasses 118 are disposed between light source

104 and interior flow portion 112 and between each photodetector 106, 108 and interior flow portion 112 to make in-line particulate detector assembly 100 serviceable in the field without interruption of fuel flow 60.

[0027] In one embodiment, second photodetector 108 is positioned in close proximity to internal flow portion 112 of housing 102 to maximize the intensity of scattered light reaching second photodetector 108.

[0028] A remote in-line particulate detector assembly 200 is shown in FIG. 3. This embodiment is similar in all respects to the in-line particulate detector assembly in FIGs. 1 and 2, except that circuitry 114 comprises a remote unit for transmitting signals from assembly 200.

[0029] A remote station 304 provides a communication base for interaction with a respective remote unit. Remote station 304 typically comprises a central interface 306, a radio frequency (RF) front-end 308, an antenna, and user interface related peripheral devices including a user interface 312, a display 314, data storage 316 and a printer 318 for enabling a user to input or extract relevant information into central interface 306. Peripheral devices as defined in this application include any device for storing particulate measurement or analysis information and intelligibly communicating the same to a system user, and include such devices as printers, hard disk drives, floppy disk drives, cathode ray tubes (CRTs) and keyboards. While only one set of respective peripheral devices is shown for a respective central interface 306, any number of peripheral drives may be utilized and are within the scope of the instant invention.

[0030] Methods for determining gas quality using remote in-line particulate detector assembly 200 are previously discussed.

[0031] Communication between remote station 304 and a respective remote unit is by way of a communications system 320, such as a "geo-synchronous" "L-band" satellite system, a "Little Leo" satellite system, a two-way paging system, a modem connection or any communication system capable of two-way communication between remote station 304 and a respective remote unit.

[0032] For the sake of good order, various aspects of the invention are set out in the following clauses:-

1. An in-line particulate detector comprising:

a housing having an inner flow portion, which housing is removably disposable between adjacent portions of pipeline to permit a fuel flow from a fuel source through said inner flow portion to a fuel consumer;

a light source disposed within said housing for emitting a light beam within said inner flow portion;

a first photodetector disposed within said hous-

ing positioned opposite and substantially normal to said light source such that substantially full strength of an unimpeded generated light beam is detected by said first photodetector;

a second photodetector disposed within said housing adjacent said first photodetector positioned such that a baseline level of an unimpeded generated light beam is detected by said second photodetector; and

circuitry coupled to said first and second photodetector to monitor the ratio of light intensities measured by said first and second photodetectors to indicate the presence of particulate within an introduced fuel flow.

2. An in-line particulate detector in accordance with clause 1, wherein said flow is natural gas.

3. An in-line particulate detector in accordance with clause 1, wherein said flow is selected from the group consisting of propane, hexane, heptane, gas derived from coal, and methane.

4. An in-line particulate detector in accordance with clause 1, wherein a fuel containing particulates will cause a generated light beam to be scattered, and the light intensity measured by second photodetector will increase above the baseline level and the light intensity reaching first photodetector will decrease.

5. An in-line particulate detector in accordance with clause 1, wherein a control structure is inputted into said circuitry.

6. An in-line particulate detector in accordance with clause 5, wherein said control structure is inputted into said circuitry by programming into memory of an application specific integrated circuit.

7. An in-line particulate detector in accordance with clause 5, wherein said control structure is inputted into said circuitry by being embedded in the form of algorithms in one or more computers.

8. An in-line particulate detector in accordance with clause 7, wherein said computer is selected from the group consisting of a workstation, a minicomputer, a microcomputer, and a supercomputer.

9. An in-line particulate detector in accordance with clause 5, wherein said control structure is programmed in a language selected from the group of C, C++, Basic, MATLAB, and FORTRAN.

10. An in-line particulate detector in accordance

with clause 5, wherein said control structure comprises the method step of:

comparing the ratio of light intensities measured by said first and second photodetectors to a setpoint ratio. 5

11. An in-line particulate detector in accordance with clause 10, wherein said ratio of light intensities exceeds said setpoint ratio and said circuitry initiates a system control. 10

12. An in-line particulate detector in accordance with clause 11, wherein said system control is to limit a turbine engine to low load operation. 15

13. An in-line particulate detector in accordance with clause 11, wherein said system control is an algorithm to look at system anomalies. 20

14. An in-line particulate detector in accordance with clause 11, wherein said system control is the activation of an alarm.

15. A remote in-line particulate detector comprising: 25

a housing having an inner flow portion, which housing is removably disposable between adjacent portions of pipeline to permit a fuel flow from a fuel source through said inner flow portion to a fuel consumer; 30

a light source disposed within said housing for emitting a light beam within said inner flow portion; 35

a first photodetector disposed within said housing positioned opposite and substantially normal to said light source such that substantially full strength of an unimpeded generated light beam is detected by said first photodetector; 40

a second photodetector disposed within said housing adjacent said first photodetector positioned such that a baseline level of an unimpeded generated light beam is detected by said second photodetector; and 45

circuitry coupled to said first and second photodetector to monitor the ratio of light intensities measured by said first and second photodetectors to indicate the presence of particulate within an introduced fuel flow; and 50

at least one remote unit for transmitting signals generated from said first and second photodetectors; 55

a central station; and

a communications link.

16. A remote in-line particulate detector in accordance with clause 15, wherein said signals represent light intensities measured by said first and photodetectors.

17. A remote in-line particulate detector in accordance with clause 15, wherein said remote system comprises a central interface coupled to said at least one remote unit, wherein said central interface is adapted to control communications between said central station and said at least one remote unit.

18. A remote in-line particulate detector in accordance with clause 15, wherein said communications link comprises a radio frequency (RF) front end.

19. A remote in-line particulate detector in accordance with clause 15 wherein said communication link comprises a satellite.

20. A remote in-line particulate detector in accordance with clause 15, wherein said communication link comprises a link.

21. A remote in-line particulate detector in accordance with clause 15 wherein said remote system further comprises an antenna.

22. A remote in-line particulate detector in accordance with clause 15 wherein said remote system further comprises at least one user interface device.

23. An in-line particulate detector comprising:

a housing having an inner flow portion, which housing is removably disposable between adjacent portions of pipeline to permit a fuel flow from a fuel source through said inner flow portion to a fuel consumer;

a means for emitting a light beam within said inner flow portion;

a first means for detecting substantially full strength of an unimpeded light beam generated by said means for emitting;

a second means for detecting a baseline level of unimpeded light beam generated by said means for emitting; and

a means for comparing the light intensities detected by said first and second means for

detecting, to determine the presence of particulate within an introduced flow.

24. An in-line particulate detector in accordance with clause 23, wherein said flow is natural gas. 5
25. An in-line particulate detector in accordance with clause 23, wherein said flow is selected from the group consisting of propane, hexane, heptane, gas derived from coal, and methane. 10
26. An in-line particulate detector in accordance with clause 23, wherein a fuel containing particulates will cause a generated light beam to be scattered, and the light intensity measured by said second means for detecting will increase above the baseline level and the light intensity reaching said first means for detecting will decrease. 15
27. An in-line particulate detector in accordance with clause 23, wherein a control structure is inputted into said circuitry. 20
28. An in-line particulate detector in accordance with clause 27, wherein said control structure is inputted into said circuitry by programming into memory of an application specific integrated circuit. 25
29. An in-line particulate detector in accordance with clause 27, wherein said control structure is inputted into said circuitry by being embedded in the form of algorithms in one or more computers. 30
30. An in-line particulate detector in accordance with clause 29, wherein said computer is selected from the group consisting of a workstation, a mini-computer, a microcomputer, and a supercomputer. 35
31. An in-line particulate detector in accordance with clause 27, wherein said control structure is programmed in a language selected from the group of C, C++, Basic, MATLAB, and FORTRAN. 40
32. An in-line particulate detector in accordance with clause 27, wherein said control structure comprises the method step of: 45
- comparing the ratio of light intensities measured by said first and second photodetectors to a setpoint ratio. 50
33. An in-line particulate detector in accordance with clause 32, wherein said ratio of light intensities exceeds said setpoint ratio and said circuitry initiates a system control. 55
34. An in-line particulate detector in accordance with clause 33, wherein said system control is to

limit a turbine engine to low load operation.

35. An in-line particulate detector in accordance with clause 33, wherein said system control is an algorithm to look at system anomalies.
36. An in-line particulate detector in accordance with clause 33, wherein said system control is the activation of an alarm.
37. An in-line particulate detector comprising: a housing having an inner flow portion;
- a light source disposed within said housing for emitting a light beam within said inner flow portion;
- a first photodetector disposed within said housing positioned opposite and substantially normal to said light source such that substantially full strength of an unimpeded generated light beam is detected by said first photodetector;
- a second photodetector disposed within said housing adjacent said first photodetector positioned such that a baseline level of an unimpeded generated light beam is detected by said second photodetector; and
- circuitry coupled to said first and second photodetector to monitor the ratio of light intensities measured by said first and second photodetectors to indicate the presence of particulate within an introduced flow.
38. An in-line particulate detector for insertion within a pipeline, said detector comprising:
- a light source to be disposed within said pipeline for emitting a light beam within an inner flow portion of said pipeline;
- a first photodetector to be disposed within said pipeline positioned opposite and substantially normal to said light source such that substantially full strength of an unimpeded generated light beam is detected by said first photodetector;
- a second photodetector to be disposed within said pipeline adjacent said first photodetector positioned such that a baseline level of unimpeded generated light beam is detected by said second photodetector; and
- circuitry coupled to said first and second photodetector to monitor the ratio of light intensities measured by said first and second photodetectors

tors to indicate the presence of particulate within an introduced flow.

Claims

1. An in-line particulate detector comprising:

a housing having an inner flow portion, which housing is removably disposable between adjacent portions of pipeline to permit a fuel flow from a fuel source through said inner flow portion to a fuel consumer;

a light source disposed within said housing for emitting a light beam within said inner flow portion;

a first photodetector disposed within said housing positioned opposite and substantially normal to said light source such that substantially full strength of an unimpeded generated light beam is detected by said first photodetector;

a second photodetector disposed within said housing adjacent said first photodetector positioned such that a baseline level of an unimpeded generated light beam is detected by said second photodetector; and

circuitry coupled to said first and second photodetector to monitor the ratio of light intensities measured by said first and second photodetectors to indicate the presence of particulate within an introduced fuel flow.

2. An in-line particulate detector in accordance with claim 1, wherein said flow is natural gas.

3. An in-line particulate detector in accordance with claim 1, wherein said flow is selected from the group consisting of propane, hexane, heptane, gas derived from coal, and methane.

4. A remote in-line particulate detector comprising:

a housing having an inner flow portion, which housing is removably disposable between adjacent portions of pipeline to permit a fuel flow from a fuel source through said inner flow portion to a fuel consumer;

a light source disposed within said housing for emitting a light beam within said inner flow portion;

a first photodetector disposed within said housing positioned opposite and substantially normal to said light source such that substantially

full strength of an unimpeded generated light beam is detected by said first photodetector;

a second photodetector disposed within said housing adjacent said first photodetector positioned such that a baseline level of an unimpeded generated light beam is detected by said second photodetector; and

circuitry coupled to said first and second photodetector to monitor the ratio of light intensities measured by said first and second photodetectors to indicate the presence of particulate within an introduced fuel flow; and

at least one remote unit for transmitting signals generated from said first and second photodetectors;

a central station; and

a communications link.

5. A remote in-line particulate detector in accordance with claim 4, wherein said signals represent light intensities measured by said first and photodetectors.

6. A remote in-line particulate detector in accordance with claim 4, wherein said remote system comprises a central interface coupled to said at least one remote unit, wherein said central interface is adapted to control communications between said central station and said at least one remote unit.

7. An in-line particulate detector comprising:

a housing having an inner flow portion, which housing is removably disposable between adjacent portions of pipeline to permit a fuel flow from a fuel source through said inner flow portion to a fuel consumer;

a means for emitting a light beam within said inner flow portion;

a first means for detecting substantially full strength of an unimpeded light beam generated by said means for emitting;

a second means for detecting a baseline level of unimpeded light beam generated by said means for emitting; and

a means for comparing the light intensities detected by said first and second means for detecting, to determine the presence of particulate within an introduced flow.

8. An in-line particulate detector in accordance with claim 7, wherein said flow is natural gas.

9. An in-line particulate detector comprising:

a housing having an inner flow portion;

a light source disposed within said housing for emitting a light beam within said inner flow portion;

a first photodetector disposed within said housing positioned opposite and substantially normal to said light source such that substantially full strength of an unimpeded generated light beam is detected by said first photodetector;

a second photodetector disposed within said housing adjacent said first photodetector positioned such that a baseline level of an unimpeded generated light beam is detected by said second photodetector; and

circuitry coupled to said first and second photodetector to monitor the ratio of light intensities measured by said first and second photodetectors to indicate the presence of particulate within an introduced flow.

10. An in-line particulate detector for insertion within a pipeline, said detector comprising:


a light source to be disposed within said pipeline for emitting a light beam within an inner flow portion of said pipeline;

a first photodetector to be disposed within said pipeline positioned opposite and substantially normal to said light source such that substantially full strength of an unimpeded generated light beam is detected by said first photodetector;

a second photodetector to be disposed within said pipeline adjacent said first photodetector positioned such that a baseline level of unimpeded generated light beam is detected by said second photodetector; and

circuitry coupled to said first and second photodetector to monitor the ratio of light intensities measured by said first and second photodetectors to indicate the presence of particulate within an introduced flow.

FIG 1







FIG 2





Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 061 356 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
10.04.2002 Bulletin 2002/15

(51) Int Cl.7: **G01N 21/53, G01N 21/85**

(43) Date of publication A2:
20.12.2000 Bulletin 2000/51

(21) Application number: **00304861.8**

(22) Date of filing: **08.06.2000**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **Dean, Anthony john**
Scotia, New York 12302 (US)
• **Shapiro, Andrew Philip**
Niskayuna, New York 12309 (US)

(30) Priority: **14.06.1999 US 333181**

(74) Representative: **Pedder, James Cuthbert et al**
GE London Patent Operation,
Essex House,
12/13 Essex Street
London WC2R 3AA (GB)

(71) Applicant: **GENERAL ELECTRIC COMPANY**
Schenectady, NY 12345 (US)

(54) **In-line particulate detector**

(57) An in-line particulate detector comprises a housing (102) having an inner flow portion. The housing (102) is disposed between adjacent portions of pipeline (50) to permit a fuel flow from a fuel source (56) through the inner flow portion to a fuel consumer (10). A light source (104) is positioned within the housing (102) for emitting a light beam within the inner flow portion. A first photodetector (106) is positioned within the housing (102) to detect the full strength of the light beam (110). A second photodetector (108) is positioned within the housing (102) to detect low, baseline levels of the light beam (110). Circuitry (114) is coupled to first and second photodetectors (106, 108) to monitor the ratio of light intensities. When a fuel containing particulates is introduced, the light beam (110) is scattered and the intensity measured by the second photodetector (108) will increase and the intensity measured by the first photodetector (106) will decrease.




FIG 2

EP 1 061 356 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 30 4861

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 4 420 256 A (FLADDA GERDT ET AL) 13 December 1983 (1983-12-13)	1-3,7-10	G01N21/53 G01N21/85
Y	* column 2, line 42 - column 3, line 2 * * column 4, line 14-63; figure 1 *	4-6	
Y	US 3 728 549 A (SACHS P) 17 April 1973 (1973-04-17) * abstract; figure 1 *	4-6	
A	US 5 828 458 A (BULL DAVID W ET AL) 27 October 1998 (1998-10-27) * column 3, line 28 - column 4, line 14 * * column 8, line 58-67; figures 1,6 *	1,7,9,10	
A	US 4 201 471 A (GREGORIG STEPHEN I N ET AL) 6 May 1980 (1980-05-06) * column 2, line 9-31; figures 1-3 *	1,7,9,10	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			G01N
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 19 February 2002	Examiner Hoogen, R
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1505 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 30 4861

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

19-02-2002

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4420256 A	13-12-1983	CA 1135074 A1	09-11-1982
		EP 0030538 A1	24-06-1981
		FI 801907 A	16-12-1980
		JP 56500707 T	21-05-1981
		SE 7905294 A	16-12-1980
		WO 8002876 A1	24-12-1980
US 3728549 A	17-04-1973	NONE	
US 5828458 A	27-10-1998	WO 9623208 A1	01-08-1996
US 4201471 A	06-05-1980	GB 1602969 A	18-11-1981
		CA 1104370 A1	07-07-1981
		DE 2836607 A1	08-03-1979
		DK 371278 A ,B,	27-02-1979
		FI 782610 A ,B,	27-02-1979
		FR 2401416 A1	23-03-1979
		IT 1118239 B	24-02-1986
		JP 1179337 C	30-11-1983
		JP 54046593 A	12-04-1979
		JP 58009374 B	21-02-1983
		NL 7808680 A	28-02-1979
		NO 782848 A ,B,	27-02-1979
		SE 429164 B	15-08-1983
		SE 7808924 A	27-02-1979
		SU 1436893 A3	07-11-1988